



The Americana Collection

VISTA

Indoor/Outdoor — ADA LED Wall Sconce

The **Vista Series** is an elegant shallow wall sconce suitable for indoor or outdoor applications exposed to the natural elements such as rain, sleet, and snow. A fully sealed and gasketed unit is protected from contaminants and foreign objects such as insects and dust while providing brilliant illumination and accent lighting.



Rectangular (REC)
Rectangular Window Option (RW)
4.5"Width x 14"Height x 2 3/4"Depth



Round (RND)
Solid Front Option (SF)
5"Width x 14"Height x 2 3/4"Depth

RAL Finishes



Pastel Orange
(RAL 2003)



Pastel Green
(RAL 6019)



Pastel Blue
(RAL 5024)



Pastel Violet
(RAL 4009)

Catalog Number	
Project Name & Location	Type



Product Specifications

BACKPLATE: 14 Ga. aluminum (AL).
SHIELD: Solid Aluminum Round or Rectangular Fascia Shield with Standard Side and Front Windows. Additional custom windows styles available - Consult Factory.
FINISH: Durable indoor/outdoor powdercoat finishes. Optional RAL colors available to choose from (www.ralcolor.com).
DRIVER: Universal Voltage 120~277V Electronic Driver, 0-10V dimming is standard.
LIGHT ENGINE: Energy Efficient LED is standard.
MOUNTING: Standard wall mount J-BOX strap.
COMPLIANCE: Built to comply with U.S. and Canadian Safety standards. Suitable for Outdoor Wet location. Complies with Buy American Act.

Applications

- HOSPITALITY
- RESTAURANTS
- THEATERS
- CONDOMINIUMS
- ENTRANCEWAYS
- VESTIBULES
- STAIRWELLS
- CORRIDORS / HALLWAYS

Order Example:
VS-RND-LED14-CT4-UNV-BZ-SF-PHTD

SERIES	
VS	Vista Series
SHAPE	
RND	Round Shield
REC	Rectangular Frame
LED WATTAGE	
LED11	11 Watt Nominal - 2000 Initial Lumens - 0-10V Low Voltage LED Dimming (100-30%)
LED14	14 Watt Nominal - 1000 Initial Lumens - 120 Volt Only, TRIAC Dimming
LED COLOR TEMPERATURE	
CT3	±3000K LED Color Temp
CT4	±4000K LED Color Temp
CT5	±5000K LED Color Temp
VOLTAGE	
UNV	120~277 Universal Volt Electronic Driver
FINISH	
BK	Black
BZ	Bronze
EPX	Epoxy Coating (Anti-Corrosion)
PA	Painted Aluminum
WHT	White
RAL	RAL Color (Visit www.ralcolor.com for choices)
CC	Custom Color (Consult Factory)
WINDOW OPTIONS	
*Custom Window Designs Available - Consult Factory	
RW	Rectangular Window
SF	Solid Front
SENSOR OPTIONS	
NOTE: Photocell/Motion Detector Options Include	
Back Box - Non-ADA	
MD	Internal Motion Detector (Single Circuit) - Specify "A" for Steps: 0% - 100% - 0% - Specify "B" for Steps: xx% - 100% - xx% xx% = LOW Level and/or STANDBY Dimmed Levels Options: 50% / 30% / 20% / 10%
PHTD	Photocell Dual Voltage - 120/277V
EMERGENCY OPTIONS	
NOTE: Integral Emergency Battery Includes	
Back Box - Non-ADA	
EM4W	Integral 4 Watt LED Emergency Battery